

LUNAPLAST™



ES-950

Lunaplast™ UL-924 Exit Signs

Lunaplast UL-924 Exit Signs, photoluminescent exit signs that require no electricity and are highly durable, are an excellent choice for both new construction and retrofit. Lunaplast UL-924 Exit Signs are Underwriters Laboratories approved to a distance of 50 feet as well as Energy Star approved. Applicable for both standard and low-location installations, Lunaplast UL-924 Exit Signs provide significant cost savings combined with 100% reliability.

Features	Technical Information	
UL-924 approved to 50-feet cUL-924 approved to 50-feet Durable and reliable Non-electrical Non-toxic, non-radioactive Shock proof Vandalism resistant Minimal installation and maintenance expense Washable Indoor only	Applications:	High and low level exit indication, Primary or supplemental installation
	Directional:	Two directional chevrons included for field application
	Code compliance:	Lunaplast UL-924 Exit Signs are compliant with a wide range of codes and standards including the following. Contact Luna to inquire about additional standards. DIN 67510-1, IMO A.752.18, ISO/CD 15370, ASTM 162, ASTM 662, ASTM E 2072-00, MIL-L-3891B, NFPA Life Safety Code 101, 1998 California Building Code and Fire Code
	Code certificates:	UL-924 approved to 50-feet cUL-924 approved to 50-feet
	Warranty:	Five year limited warranty

Product Identification	Materials	Sizes	Colors
Lunaplast UL-924 Exit Sign	ES-950 5000SR	8" x 13.625"	G R
Lunaplast UL-924 Exit Sign (Large)	ES-952 5000ER	9.5" X 16"	R

Material Codes

5000SR Semi-Rigid

Color Codes

G (Green) R (Red)